

SWIFT O MATIC PRESTIGE

VALVOLA MOTORIZZATA CON DISTANZIALE PER COIBENTAZIONE
 MOTORIZED BALL VALVE WITH EXTENSION FOR INSULATION



**Valvola motorizzata con distanziale
 adatto per applicazione diretta della coibentazione sulla valvola**

- Disponibile con motore 230Vac - 24 Vac - 24 Vdc
- Valvola bocchettonate 2 e 3 vie da 1/2" a 1" 1/4

Ball valve with extension for insulation with electrical actuator

- 230Vac - 24 Vac - 24 Vdc available
- 2-way and 3-way valve with tail and nut from 1/2" to 1" 1/4

R2651

Kit distanziatore
 Kit spacer



**CODICE
 CODE**

**MISURA
 SIZE**

R2651X00

-

Kit distanziatore in acciaio AISI 304 e perno CW724R, ISO 5211 F03/F04 per attuatore FLAT ISO e valvole con attacco QM
 Spacer in stainless steel AISI 304 and CW724R spindle, ISO 5211 F03/F04 for actuator FLAT ISO and quick mounting valves.

R2834 - R2842-R2877

ATTUATORE ELETTRICO
 ELECTRIC ACTUATOR



CARATTERISTICHE ATTUATORE

R2834P06 Flat ISO 24DC SPST/IP65/scaldiglia e sblocco manuale. Manovra 5sec/90°

R2842P06 Flat ISO 24VAC SPST/IP65/scaldiglia e sblocco manuale. Manovra 60sec/90°

R2877P06 Flat ISO 230VAC SPST/IP65/scaldiglia e sblocco manuale. Manovra 60sec/90°

FEATURES OF THE ACTUATOR

R2834P06 Flat ISO 24DC SPST/IP65/heater and manual override. Operating time 5 sec/90°

R2842P06 Flat ISO 24VAC SPST/IP65/heater and manual override. Operating time 60 sec/90°

R2877P06 Flat ISO 230VAC SPST/IP65/heater and manual override. Operating time 60 sec/90°

ISO 5211

**CODICE
 CODE**

**MISURA
 SIZE**

R2834P06

1/2" - 1" 1/4

R2842P06

1/2" - 1" 1/4

R2877P06

1/2" - 1" 1/4

GUARDA IL VIDEO / WATCH THE VIDEO



Attuatore IP65 con scaldiglia anti condensa 230Vac- 24Vdc - 24Vac
 Electric actuator IP65 with heater 230Vac- 24Vdc - 24Vac

